

**Lightweight ATEX-rated rechargeable lantern weighs just 875 grams.  
 It produces a tight beam that is optimal for firefighting operations.**



<p>High, low and blink modes:</p> <ul style="list-style-type: none"> <li>- High for a bright, far-reaching beam: 180 lumens; 100,000 candela; 632m beam; runs 3.5 hours</li> <li>- Low for a less intense beam and longer run time: 70 lumens; 40,000 candela; 400m beam; runs 7.5 hours</li> <li>- Blink for signaling: runs 5.5 hours</li> </ul>
<ul style="list-style-type: none"> <li>- Deep-dish parabolic reflector produces a tight beam with optimum peripheral illumination to aid in navigation</li> <li>- Optimized electronics provide regulated intensity</li> </ul>
<p>IP66; dust tight and water-resistant; 2m impact resistance tested</p>
<p>19.76 cm (7.78"); 875 grams (1.93 lbs)</p>

<p><b>ATEX:</b> II 3G Ex ic nA IIC T5 Gc II 3D Ex tc IIIC T54°C Dc FTZU 08 ATEX 0139X  <b>IECEx:</b> Ex ic nA IIC T5 Gc Ex tc IIIC T54°C Dc IECEx FTZU 15.0038X  <b>InMetro:</b> Ex nA ic IIC T5 Gc Ex tc IIIC T54°C Dc IP66 DNV 16.0076X          Rack meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position</p>
<p>Limited Lifetime Warranty          Visit <a href="http://streamlight.com">streamlight.com</a> for full warranty information</p>
<p>#44753 - Vulcan LED ATEX Standard System - 230V AC/12V DC - Orange          #44758 - Vulcan LED Standard System - 230V AC/12V DC - Orange - InMetro          #44752 - Vulcan LED ATEX Standard System -240V AC/12V DC - Orange          #44754 - Vulcan LED ATEX Standard System - 100V/120V AC/12V DC - Orange          #44751 - Vulcan LED ATEX Vehicle Mount System 12V DC - Orange          #44756 - Vulcan LED Vehicle Mount System 12V DC - Orange - InMetro          #44750 - Vulcan LED ATEX Light Only - Orange          #44755 - Vulcan LED Light Only - Orange - InMetro</p>